

# BB 円筒型 誘導炉るつぼ

## Cylindrical Type For Induction Furnaces

2024/2/29Update

製品仕様		製品外径サイズ Outside Diameter mm			全容量 リットル	溶湯目安重量 Kg	
型名	番型 No.	口径 TOP	底径 Bottom	高さ Hight		アルミ	黄銅
A	# 4750	930	910	1485	713	1520	4750
A	# 4000	848	820	1500	577	1280	4000
A	# 3400	845	820	1350	466	1090	3400
A	# 3000	840	820	1200	444	960	3000
A	# 2800	747	730	1300	377	900	2800
AN	# 2000	743	730	1000	275	640	2000
A	# 1600	690	670	1000	234	510	1600
AO	# 2600	660	620	1600	333	830	2600
AY	# 2100	652	620	1300	276	670	2100
AO	# 1500	645	620	1000	209	480	1500
A	# 1000	574	550	950	153	320	1000
AF	# 1000	488	470	1310	153	320	1000
AF	# 900	485	470	1120	142	290	900
A	# 650	480	470	700	77	210	650
AP	# 900	518	280	915	142	290	900
A	# 750	513	495	800	100	240	750
A	# 660	460	450	786	85	210	660
AB	# 500	460	450	680	70	160	500
AO	# 550	433	415	847	69	180	550
AM	# 500	432	415	800	60	160	500
AE	# 350	390	386	640	50	120	350
A	# 280	389	386	560	42	90	280
A	# 150	310	307	450	19	50	150
A	# 135	310	307	400	16	50	140
AK	# 120	256	251	565	19	40	120
AK	# 100	255	251	490	16	40	100
AK	# 80	254	251	415	13	30	80
A	# 80	220	217	500	9	30	80
A	# 60	218	217	400	7	20	60